

# Package: tarflow.iquizoo (via r-universe)

August 21, 2024

**Title** Setup ``targets" Workflows for ``iquizoo" Data Processing

**Version** 3.12.2

**Description** For ``iquizoo" data processing, there is already a package called ``preproc.iquizoo", but eventually the use of it is relied on a workflow. This package is used to build such workflows based on tools provided by ``targets" package which mimics the logic of ``make", automating the building processes.

**License** Apache License (>= 2)

**URL** <https://psychelzh.github.io/tarflow.iquizoo/>,  
<https://github.com/psychelzh/tarflow.iquizoo>

**BugReports** <https://github.com/psychelzh/tarflow.iquizoo/issues>

**Depends** R (>= 4.1.0)

**Imports** cachem, cli, DBI, glue, jsonlite, memoise, rlang (>= 1.0.0),  
tarchetypes, targets

**Suggests** bit64, covr, data.iquizoo (>= 2024.7.14), digest, lifecycle,  
odbc, preproc.iquizoo (>= 2.6.0), RMariaDB (>= 1.3.1),  
roxygen2, testthat (>= 3.0.0), tibble

**Remotes** psychelzh/data.iquizoo, psychelzh/preproc.iquizoo

**Config/testthat/edition** 3

**Config/testthat/parallel** true

**Config/testthat/start-first** targets

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**Repository** <https://psychelzh.r-universe.dev>

**RemoteUrl** <https://github.com/psychelzh/tarflow.iquizoo>

**RemoteRef** HEAD

**RemoteSha** 2b1584318af4571f876313d2afced13ea2fd1d5c

## Contents

|                                 |    |
|---------------------------------|----|
| check_source . . . . .          | 2  |
| fetch_data . . . . .            | 3  |
| fetch_iquizoo . . . . .         | 4  |
| fetch_iquizoo_mem . . . . .     | 4  |
| get_users_props_names . . . . . | 5  |
| parse_data . . . . .            | 5  |
| setup_option_file . . . . .     | 6  |
| setup_source . . . . .          | 7  |
| setup_templates . . . . .       | 7  |
| tar_fetch_data . . . . .        | 8  |
| tar_fetch_users . . . . .       | 9  |
| tar_prep_hash . . . . .         | 9  |
| tar_prep_iquizoo . . . . .      | 10 |
| tar_prep_raw . . . . .          | 11 |
| use_targets_pipeline . . . . .  | 12 |

|              |           |
|--------------|-----------|
| <b>Index</b> | <b>13</b> |
|--------------|-----------|

---

|              |  |
|--------------|--|
| check_source | <i>Check if the database based on the given data source is ready</i> |
|--------------|--|

---

### Description

Check if the database based on the given data source is ready

### Usage

```
check_source(source = setup_source())
```

### Arguments

source            The data source from which data is fetched. See [setup\\_source\(\)](#) for details.

### Value

TRUE if the database is ready, FALSE otherwise.

---

|            |   |
|------------|---|
| fetch_data | <i>Fetch data from iQuizoo database</i> |
|------------|---|

---

### Description

This function is a wrapper of `fetch_iquizoo()`, which is used as a helper function to fetch data from the iQuizoo database.

### Usage

```
fetch_data(  
  project_id,  
  game_id,  
  ...,  
  what = c("raw_data", "scores"),  
  query = NULL,  
  suffix_format = "%Y0101"  
)
```

### Arguments

|                            |  |
|----------------------------|--|
| <code>project_id</code>    | The project id to be bound to the query.   |
| <code>game_id</code>       | The game id to be bound to the query.  |
| <code>...</code>           | Further arguments passed to <code>fetch_iquizoo()</code> .   |
| <code>what</code>          | What to fetch. Can be either "raw_data" or "scores".   |
| <code>query</code>         | A parameterized SQL query. A default query file is stored in the package, which is often enough for most cases. You can also specify your own query file by this argument. See details for more information. |
| <code>suffix_format</code> | The format of the date suffix. See details for more information.   |

### Details

The data essentially means one of the two types of data: raw data or scores. The raw data is the original data collected from the game, while the scores are the scores calculated by the iQuizoo system. While scores can also be calculated from the raw data, the pre-calculated scores are used to for some quick analysis.

The data is separated by project date, so the table name is suffixed by the project date, which is automatically fetched from the database by this function. You could set the format of the date suffix by `suffix_format`, although currently you should not need to change it because it probably will not change in the future. Finally, this suffix should be substituted into the query, which should contain an expression to inject the table name, i.e., "{table\_name}".

### Value

A `data.frame` contains the fetched data.

---

|               |  |
|---------------|--|
| fetch_iquizoo | <i>Fetch result of query from iQuizoo database</i> |
|---------------|--|

---

### Description

Fetch result of query from iQuizoo database

### Usage

```
fetch_iquizoo(query, ..., params = NULL, source = setup_source())
```

### Arguments

|        |   |
|--------|---|
| query  | A character string containing SQL.  |
| ...    | Further arguments passed to <a href="#">DBI::dbConnect()</a> .  |
| params | The parameters to be bound to the query. Default to NULL, see <a href="#">DBI::dbGetQuery()</a> for more details. |
| source | The data source from which data is fetched. See <a href="#">setup_source()</a> for details.                       |

### Value

A [data.frame](#) contains the fetched data.

### See Also

[fetch\\_iquizoo\\_mem\(\)](#) for a memoised version of this function.

---

|                   |  |
|-------------------|--|
| fetch_iquizoo_mem | <i>Memoised version of <a href="#">fetch_iquizoo()</a></i> |
|-------------------|--|

---

### Description

This function is a memoised version of [fetch\\_iquizoo\(\)](#). It is useful when the same query is called multiple times or you want to cache the result. See [memoise::memoise\(\)](#) and [fetch\\_iquizoo\(\)](#) for more details.

### Usage

```
fetch_iquizoo_mem(cache = NULL)
```

**Arguments**

cache            The cache to be used. Default cache could be configured by setting the environment variable TARFLOW\_CACHE to "disk" or "memory". If set TARFLOW\_CACHE to "disk", the cache will be stored in disk at ~/.cache/tarflow.iquizoo with a maximal age of 7 days. If set TARFLOW\_CACHE to "memory", the cache will be stored in memory. You can also set cache to a custom cache, see [memoise::memoise\(\)](#) for more details.

**Value**

A memoised version of [fetch\\_iquizoo\(\)](#).

**See Also**

[fetch\\_iquizoo\(\)](#) for the original function.

---

get\_users\_props\_names    *Get the names of the user properties.*

---

**Description**

Get the names of the user properties.

**Usage**

```
get_users_props_names()
```

**Value**

A character vector of the names.

---

parse\_data                *Parse Raw Data*

---

**Description**

Raw data fetched from iQuizoo database is stored in json string format. This function is used to parse raw json string data as [data.frame\(\)](#) and store them in a list column.

**Usage**

```
parse_data(data, col_raw_json = "game_data", name_raw_parsed = "raw_parsed")
```

**Arguments**

|                 |   |
|-----------------|---|
| data            | The raw data.                                 |
| col_raw_json    | The column name storing raw json string data. |
| name_raw_parsed | The name used to store parsed data.           |

**Value**

A [data.frame](#) contains the parsed data.

---

|                   |  |
|-------------------|--|
| setup_option_file | <i>Setup MySQL database connection option file</i> |
|-------------------|--|

---

**Description**

This function will create a MySQL option file at the given path. To ensure it works, set these environment variables before calling this function:

- MYSQL\_HOST: The host name of the MySQL server.
- MYSQL\_USER: The user name of the MySQL server.
- MYSQL\_PASSWORD: The password of the MySQL server.

**Usage**

```
setup_option_file(path = NULL, overwrite = FALSE, quietly = FALSE)
```

**Arguments**

|           |  |
|-----------|--|
| path      | The path to the option file. Default location is operating system dependent. On Windows, it is C:/my.cnf. On other systems, it is ~/.my.cnf. |
| overwrite | Whether to overwrite the existing option file.   |
| quietly   | A logical indicates whether message should be suppressed.  |

**Value**

NULL (invisible).

---

|              |                        |
|--------------|------------------------|
| setup_source | <i>Set data source</i> |
|--------------|------------------------|

---

**Description**

Set data source

**Usage**

```
setup_source(
  driver = getOption("tarflow.driver"),
  dsn = getOption("tarflow.dsn"),
  group = getOption("tarflow.group")
)
```

**Arguments**

|        |  |
|--------|--|
| driver | The driver used. Set as an option of "tarflow.driver". Options are <code>odbc::odbc()</code> and <code>RMariaDB::MariaDB()</code> , both of which need pre-configurations. Default to first available one. |
| dsn    | The data source name of an <b>ODBC</b> database connector. See <code>odbc::dbConnect()</code> for more information. Used when driver is set as <code>odbc::odbc()</code> .                                 |
| group  | Section identifier in the default.file. See <code>RMariaDB::MariaDB()</code> for more information. Used when driver is set as <code>RMariaDB::MariaDB()</code> .   |

**Value**

An S3 class of tarflow.source with the options.

---

|                 |  |
|-----------------|--|
| setup_templates | <i>Set up templates used to fetch data</i> |
|-----------------|--|

---

**Description**

If you want to extract data based on your own parameters, you should use this function to set up your own SQL templates. Note that the SQL queries should be parameterized.

**Usage**

```
setup_templates(
  contents = NULL,
  users = NULL,
  raw_data = NULL,
  scores = NULL,
  progress_hash = NULL
)
```

**Arguments**

|               |   |
|---------------|---|
| contents      | The SQL template file used to fetch contents. At least <code>project_id</code> and <code>game_id</code> columns should be included in the fetched data based on the template. <code>project_id</code> will be used as the only parameter in <code>users</code> and <code>project</code> templates, while all three will be used in <code>raw_data</code> and <code>scores</code> templates. |
| users         | The SQL template file used to fetch users. Usually you don't need to change this.   |
| raw_data      | The SQL template file used to fetch raw data. See <a href="#">fetch_data()</a> for details. Usually you don't need to change this.  |
| scores        | The SQL template file used to fetch scores. See <a href="#">fetch_data()</a> for details. Usually you don't need to change this.  |
| progress_hash | The SQL template file used to fetch progress hash. Usually you don't need to change this.   |

**Value**

A S3 object of class `tarflow.template` with the options.

---

|                |  |
|----------------|--|
| tar_fetch_data | <i>Generate a set of targets for fetching data</i> |
|----------------|--|

---

**Description**

This target factory is the main part of the `tar_prep_iquizoo` function. It fetches the raw data and scores for each project and task/game combination.

**Usage**

```
tar_fetch_data(
  contents,
  what = c("raw_data", "scores"),
  templates = setup_templates(),
  check_progress = TRUE
)
```

**Arguments**

|                |   |
|----------------|---|
| contents       | The contents structure used as the configuration of data fetching.  |
| what           | What to fetch.  |
| templates      | The SQL template files used to fetch data. See <a href="#">setup_templates()</a> for details.   |
| check_progress | Whether to check the progress hash. If set as <code>TRUE</code> , Before fetching the data, the progress hash objects named as <code>progress_hash_{project_id}</code> will be depended on, which are typically generated by <a href="#">tar_prep_hash()</a> . If the projects are finalized, set this argument as <code>FALSE</code> . |



**Value**

A list of target objects.

---

|                 |  |
|-----------------|--|
| tar_fetch_users | <i>Generate a set of targets for fetching user information</i> |
|-----------------|--|

---

**Description**

The user information is used to identify the users involved in the project.

**Usage**

```
tar_fetch_users(
  contents,
  subset_users_props = NULL,
  templates = setup_templates(),
  check_progress = TRUE
)
```

**Arguments**

|                    |   |
|--------------------|---|
| contents           | The contents structure used as the configuration of data fetching.  |
| subset_users_props | The subset of user properties to be fetched. See <a href="#">get_users_props_names()</a> for all the available properties. If NULL, all properties will be fetched. |
| templates          | The SQL template files used to fetch data. See <a href="#">setup_templates()</a> for details.   |
| check_progress     | Whether to check the progress hash. Set it as FALSE if the project is finalized.  |

**Value**

A list of target objects.

---

|               |   |
|---------------|---|
| tar_prep_hash | <i>Generate a set of targets for fetching progress hash</i> |
|---------------|---|

---

**Description**

The progress hash stores the progress of the project, which is used to check whether the project is updated.

**Usage**

```
tar_prep_hash(contents, templates = setup_templates())
```

**Arguments**

contents            The contents structure used as the configuration of data fetching.  
 templates           The SQL template files used to fetch data. See `setup_templates()` for details.

**Details**

These objects are named as `progress_hash_{project_id}` for each project.

**Value**

A list of target objects.

---

|                               |   |
|-------------------------------|---|
| <code>tar_prep_iquizoo</code> | <i>Generate a set of targets for pre-processing of iQuizoo data</i> |
|-------------------------------|---|

---

**Description**

This target factory prepares a set of target objects used to fetch data from iQuizoo database, separated into static branches so that each is for a specific project and task/game combination. Further pre-processing on the fetched data can also be added if requested.

**Usage**

```
tar_prep_iquizoo(
  params,
  contents,
  ...,
  what = c("raw_data", "scores"),
  action_raw_data = c("all", "parse", "none"),
  combine = NULL,
  subset_users_props = NULL,
  templates = setup_templates(),
  check_progress = TRUE,
  cache = NULL
)
```

**Arguments**

params, contents

Used as the configuration of data fetching. These two arguments are mutually exclusive. If `params` is specified, it will be used as parameters to be bound to the query, see `DBI::dbBind()` for more details. The default template requires specifying `organization_name`, `project_name`, `course_name` and `game_name`, in that order. Set the column as `NA` to skip that parameter. If `contents` is specified, it should be a [data.frame](#) and will be used directly as the configuration of data fetching. Note `contents` should at least contain `project_id` and `game_id` names.

|                    |  |
|--------------------|--|
| ...                | For future usage. Should be empty.   |
| what               | What to fetch. There are basically two types of data, i.e., raw data and scores. The former is the logged raw data for each trial of the tasks/games, and further actions on the fetched raw data can be specified by <code>action_raw_data</code> . The latter is the scores calculated by iQuizoo server.  |
| action_raw_data    | The action to be taken on the fetched raw data. There are two consecutive actions, i.e., raw data parsing and pre-processing. The former will parse the json formatted raw data into <code>data.frame()</code> s and wrap them into one list column, see <code>parse_data()</code> for more details. The latter will calculate indices based on the parsed data, see <code>preproc.iquizoo::preproc_data()</code> for more details. If set as "none", neither will be done. If set as "parse", only raw data parsing will be done. If set as "all", both parsing and pre-processing will be done. If what is set as "scores", this argument will be ignored. |
| combine            | Specify which targets to be combined. Note you should only specify names from <code>c("scores", "raw_data", "raw_data_parsed", "indices")</code> . If NULL, none will be combined.   |
| subset_users_props | The subset of user properties to be fetched. See <code>get_users_props_names()</code> for all the available properties. If NULL, all properties will be fetched.   |
| templates          | The SQL template files used to fetch data. See <code>setup_templates()</code> for details.   |
| check_progress     | Whether to check the progress hash. Set it as FALSE if the project is finalized.   |
| cache              | The cache to be used in <code>fetch_iquizoo_mem()</code> .   |

**Value**

A list of target objects.

---

|              |  |
|--------------|--|
| tar_prep_raw | <i>Generate a set of targets for wrangling and pre-processing raw data</i> |
|--------------|--|

---

**Description**

This target factory is the main part of the `tar_prep_iquizoo` function. It wrangles the raw data into a tidy format and calculates indices based on the parsed data.

**Usage**

```
tar_prep_raw(
  contents,
  action_raw_data = c("parse", "preproc"),
  name_data = "raw_data",
  name_parsed = "raw_data_parsed",
  name_indices = "indices"
)
```

**Arguments**

|                 |  |
|-----------------|--|
| contents        | The contents structure used as the configuration of data fetching. |
| action_raw_data | The action to be taken on the fetched raw data.                    |
| name_data       | The name of the raw data target.                                   |
| name_parsed     | The name of the parsed data target.                                |
| name_indices    | The name of the indices target.                                    |

**Value**

A list of target objects.

---

use\_targets\_pipeline *Create standard data fetching targets pipeline script*

---

**Description**

This function creates a standard data fetching targets pipeline script for you to fill in.

**Usage**

```
use_targets_pipeline()
```

**Value**

NULL (invisible). This function is called for its side effects.

# Index

`check_source`, 2

`data.frame`, 3, 4, 6, 10  
`data.frame()`, 5, 11  
`DBI::dbBind()`, 10  
`DBI::dbConnect()`, 4  
`DBI::dbGetQuery()`, 4

`fetch_data`, 3  
`fetch_data()`, 8  
`fetch_iquizoo`, 4  
`fetch_iquizoo()`, 3–5  
`fetch_iquizoo_mem`, 4  
`fetch_iquizoo_mem()`, 4, 11

`get_users_props_names`, 5  
`get_users_props_names()`, 9, 11

`memoise::memoise()`, 4, 5

`odbc::dbConnect()`, 7  
`odbc::odbc()`, 7

`parse_data`, 5  
`parse_data()`, 11  
`preproc.iquizoo::preproc_data()`, 11

`RMariaDB::MariaDB()`, 7

`setup_option_file`, 6  
`setup_source`, 7  
`setup_source()`, 2, 4  
`setup_templates`, 7  
`setup_templates()`, 8–11

`tar_fetch_data`, 8  
`tar_fetch_users`, 9  
`tar_prep_hash`, 9  
`tar_prep_hash()`, 8  
`tar_prep_iquizoo`, 10  
`tar_prep_raw`, 11

`use_targets_pipeline`, 12